



INSTRUCTIONS

-J01915

REV. 2-3-00

Kit Number 53249-01

TOUR-PAK LID ORGANIZER KIT

General

This Tour-Pak Lid Organizer kit is designed to fit all King and Chopped Tour-Paks.

WARNING

Maximum load capacity of the lid organizer is 5 lbs (2.3 Kg). The combined load of lid organizer and Tour-Pak must not exceed weight of 25 lbs (11.3 kg). Overloading the motorcycle could cause unstable handling which could result in loss of control of vehicle and death or serious injury.

NOTE

This Tour-Pak Lid Organizer kit will not work with Mini Tour-Pak Lid Rack (P/N 53100-96), Tour-Pak Spoiler Kit w/light (P/N 53149-series), Tour-Pak Spoiler Kit without light (P/N 53150-series), or Tour-Pak Top Rack Kit (P/N 53661-86T).

NOTE

If Tour-Pak is equipped with Utility Light (P/N 90270-99) installed on the inside surface, it will need to be relocated.

Kit Contents:

Qty	Description	Part Number
1	Organizer, tour-pak lid	Not sold separately
1	Wipe, alcohol	94678-00Y
1	Label, load limit	90821-74A

Installation

- If Premium Tour-Pak Luggage Rack (P/N 53665-87) or Nostalgic Tour-Pak Lid Rack (P/N 53101-96) is installed, perform the following Step a. If not, proceed to Step 2.
 - Check the Luggage Rack Mounting Screws for proper torque. Tighten at this time, if necessary, since mounting hardware will become inaccessible after lid organizer is installed.
- If Tour-Pak Light (P/N 54302-98) is installed, perform the following Steps a and b. If not, proceed to Step 3.
 - Remove the light from the Tour-Pak Lid sidewall and unclip wiring from adhesive backed clips. Set the light in the Tour-Pak bottom.
 - If installed, remove adhesive-backed clips from the Tour-Pak Lid surface, leaving clips attached to sidewall in place.
- Using the isopropyl alcohol wipe included in kit, thoroughly clean the Lid surface. Make sure any leftover adhesive is removed, then allow to dry completely. Make sure surface is free of condensed moisture.

NOTE
The ideal temperature range for applying the tape is 70 to 100 degrees F (21 to 38 degrees C). Minimum application temperature is 50 degrees F (10 degrees C). If you attempt to apply the tape below these temperatures, the adhesive will become too firm to adhere readily.
- Locate the double-sided tape on back of the Lid Organizer and remove the backing material.

NOTE
When performing the next Step, be sure to apply pressure to entire length of tape to ensure proper activation of pressure-sensitive adhesive.
- Carefully center the Lid Organizer in Tour-Pak Lid recess and press firmly into place. While applying opposing force from outside of lid (to minimize force on tether, hinges, etc.), apply moderate pressure around entire perimeter of organizer and in middle (making sure to include all areas of tape contact).
- Allow tape to cure ("wet-out") for a minimum of 48 hours at 70 degrees F (allow extra time if temp is below 70 degrees). Do not place items in the Lid Organizer while adhesive is curing.
- If applicable, re-install Tour-Pak Light (P/N 54302-98) to Lid sidewall. Replace adhesive-backed clips (reorder P/N 10102) on lid sidewall, and place wiring into clips.
- Install load limit label on inside of Tour-Pak on lid or base sidewall in a readily visible location.